

CHAEVI

7kW Charger

DCV-3WB7C

Model	DCV-3WC7C-V2
Dimensions	360(W) x 130(D) x 455(H)
Charger Type	B Type + C Type (SAEJ1772 (7pin))
IP	IP44
Input Specification	220Vac, 32A, 60Hz, 7kW
Output Specification	220Vac, 32A, 60Hz, 7kW
Display	4-inch Touchscreen
User Authentication	Membership card, Credit card, Digital wallet, QR
Service	Control operation, Charging Service(reservation)
Feature	Output control for peak load
Accessories	Canopy, Stand, Cable Hanger

CHAEVI

7kW Charger

DCV-3BB7C

Model	DCV-3BB7C-V2C-M / DCV-3BB7C-V2B-M
Dimensions	630(W) x 325(D) x 1,400(H)
Charger Type	B Type + C Type (SAEJ1772 (7pin))
IP	IP44
Input Specification	220Vac, 32A, 60Hz, 7kW
Output Specification	220Vac, 32A, 60Hz, 7kW
Display	8-inch LCD
User Authentication	Membership card, Credit card, QR Code
Service	Control Operation, Affordable Charging Service(reservation)
Feature	Output control for peak load
Accessories	Canopy

CHAEVI

50kW - 3CH Fast Charger

DCV-3FT50P

Model	DCV-3FT50P-UC-M / DCV-3FT50P-UB-M
Dimensions	600(W) x 715(D) x 1,555(H)
Charger Type	CCS-2, CHAdeMO, AC 3phase(Type2)
IP	IP54
Input Specification	3 phase 4wire, 380Vac, 85A, 50/60Hz, 53kW
Output Specification	CCS2 : DC 150V-1000V, 0-125A, 50kW CHAdeMo : DC 150V-500V, 0-125A, 50kW AC 3-phase : 380Vac, 0-63A, 50/60Hz, 43kW
Display	15-inch Touchscreen / Charging indicator – LED
User Authentication	Membership card, Credit card, Digital wallet, QR
Service	Control operation, Charging Service(reservation)
Feature	Output control for peak load
Accessories	Canopy

CHAEVI

100kW - 2CH Fast Charger

DCV-3FD100P

Model	DCV-3FD100P-UC-M / DCV-3FD100P-UB-M
Dimensions	500(W) x 715(D) x 1,500(H)
Charger Type	CCS2 + CCS2
IP	IP54
Input Specification	3phase 4wire, 380Vac, 162A, 60Hz, 106kW
Output Specification	DC 150V-1000V, 0-200A, 100kW(Simultaneous Charging)
Display	15-inch LCD Touchscreen
User Authentication	Membership card, Credit card, Digital wallet, QR
Service	Control operation, Charging Service(reservation)
Feature	Output control for peak load
Accessories	Canopy

CHAEVI

200kW - 2CH Fast Charger

DCV-3FD200P

Model	DCV-3FD200P-UC-M / DCV-3FD200P-UB-M
Dimensions	700(W) x 800(D) x 1,850(H)
Charger Type	CCS2 + CCS2
IP	IP54
Input Specification	3 phase 4wire, 380Vac, 327A, 60Hz, 215kW
Output Specification	DC 150V-1000V, 0-200A, 200kW(Simultaneous Charging)
Display	15-inch LCD Touchscreen
User Authentication	Membership card, Credit card, Digital wallet, QR
Service	Control operation, Charging Service(reservation)
Feature	Output control for peak load
Accessories	Canopy

ICONIC

400kW (Ultra Fast Charger [Dispenser])

DCV-3FNHOC-U

300kW, 320kW, 350kW, 400kW (Wide range of coverage)

Model	DCV-3FNHOC-U
Dimensions	600(W) x 600(D) x 2,630(H)
Charger Type	CCS1 & CCS2
IP	IP54
Input Specification	DC 150V-1000V, 0-400A (Max)
Output Specification	DC 150V-1000V, 0-400A (Max)
Display	15-inch LCD Touchscreen , LED
User Authentication	Membership card, Credit card, QR Code
Service	Control Operation, Affordable Charging Service(reservation)
Feature	Liquid Cooling System (Connector, Cooler) Turn Cable, Side handle